



## UC300 S24 Cat.5e LSHF D<sub>ca</sub>



### Application

Primary (Campus), Secondary (Riser), Tertiary (Horizontal)  
 IEEE 802.3: 10Base-T; 100Base-T; 1000Base-T;  
 IEEE 802.5 16 MB; ISDN; TPDDI; ATM  
 Power over Ethernet (PoE) / PoE+

### Standards

EN 50173-1; EN 50288-2-1  
 ISO/IEC 11801; IEC 61156-5  
 TIA/EIA-568-C.2  
 IEEE 802.3at

### Flame resistance

EN 50399: Class Dcas2d2a1; Class Eca  
 LSHF (LSOH): IEC 60332-1; IEC 60754-2; IEC 61034

### Construction

Conductor	bare copper wire, Ø 0.51 mm (AWG24/1)
Insulation	PE, Ø 1.1 mm
Twisting	2 cores to the pair
Cable lay up	4 pairs to the core
Screen	Al-laminated plastic foil, Drain wire AWG26 tinned
Sheath	LSHF D <sub>ca</sub> , grey RAL 7035

### Mechanical properties

Bending radius	without load	4 x D
	with load	8 x D
Temperature range	during operation	-20°C to + 60°C
	during installation	0°C to + 50°C



A brand of the

**Prysmian**  
 Group

## UC300 S24 Cat.5e LSHF D<sub>ca</sub>

### Electrical properties

at 20°C ± 5°C

Loop resistance		≤ 190 Ω/km
Resistance unbalance		≤ 2%
Insulation resistance	(500 V)	≥ 2000 MΩxkm
Mutual capacitance	at 800 Hz	Nom. 48 nF/km
Capacitance unbalance	(pair/ground)	≤ 1500 pF/km
Mean characteristic impedance	100 MHz	100 ± 5 Ω
Nominal velocity of propagation		ca. 67%
Propagation delay		≤ 535 ns/100 m
Delay skew		≤ 20 ns/100 m
Test voltage	(DC, 1 min) core/core and core/screen	1000 V
Transfer impedance	at 1 MHz	≤ 50 mΩ /m
	at 10 MHz	≤ 100 mΩ /m
	at 30 MHz	≤ 200 mΩ /m
Coupling attenuation		≥ 55 dB
Segregation class		"c"

### Electrical data (nominal)

acc. to Cat.5e (at 20°C)

F (MHZ)	Attenuation (dB/100m)	NEXT (dB)	PS-NEXT (dB)	ACR (dB/100m)	PS-ACR (dB/100m)	ACRF (dB/100m)	PS-ACRF (dB/100m)	Return loss (dB)
1.0	1.9	71	68	69.1	66.1	68	65	20
4.0	3.7	62	59	58.3	55.3	56	53	23
10.0	6.0	56	53	50.0	47.0	48	45	25
16.0	7.6	53	50	45.4	42.4	44	41	25
20.0	8.5	51	48	42.5	39.5	42	39	25
31.2	10.7	49	46	38.3	35.3	38	35	24
62.5	15.7	44	41	28.3	25.3	32	29	22
100.0	19.8	41	38	21.2	18.2	28	25	20
125.0	22.3	40	37	17.7	14.7	26	23	19
155.5	24.2	38	35	13.8	10.8	24	21	
175.0	25.7	37	34	11.3	8.3	23	20	
200.0	27.5	36	33	8.5	5.5	22	19	
250.0	29.2	35	32	5.8	2.8	20	17	
300.0	32.0	34	31	2.0	-1.0	16	13	



ALIOPOLIS

35 RUE D'ILLZACH  
68100 MULHOUSE  
+33 389 317 347  
contact@aliopolis.eu

# FICHE TECHNIQUE



A brand of the  
**Prysmian**  
Group

## UC300 S24 Cat.5e LSHF D<sub>ca</sub>

Product name	Outer diameter mm	Euro Class	Fire load		Weight kg/km	Copper index	Tensile force N
			MJ/km	kWh/m			
UC300 S24 Cat.5e F/UTP LSHF D <sub>ca</sub> 305BR	5.9	D <sub>ca</sub> s2d2a1	415	0,119	38	19.8	100

© PRYSMIAN GROUP 2011, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.